

STORAGE UNITS



- Code: FTM 1007 019
- Description: Tables in two structures with legs or with loop frame



① Sliding door

② Integrated runner system, Surface totally usable Embossed handles

③ Height adjustable shelves each 32 mm

④ Fitted handles by injected aluminium

⑤ Drawers with total extraction


⑥ Feet with inner levelers

⑦ Optional: Steel side by 2 mm thickness

⑧ Cable access Ø 80 mm


⑨ Anti-skid support

Assemble system by modules (Reversible)




STORAGE UNITS


· 2 sliding doors





· Drawers/Door



· Door/Drawers




HUTCH IN OPTION



■ STORAGE UNITS



MFC frame composed by reversible modular system with shelves, sliding doors and or drawers and filing drawers. Two different models:

• Model with shelves and sliding doors




- 1 Top and base, 25 mm thickness
- 2 Inner side panels, mfc 19 mm thickness. Back panel 16 mm thickness
- 3 Shelves are manufactured by mfc 16 mm thickness. Height adjustable every 32 mm
- 4 Ergonomic handles produced with Zamak, aluminium alloy.
- 5 Top security lock. Two positions, open and close. Possibility of a unique key
- 6 Levelers supports, inner easy access +20 mm
- 7 Anti skid PVC cap included in the levellers
- 8 2 cable access Ø80 mm, PVC top cover
- 9 MFC sliding door 16 mm thickness
- 10 Thermoplastic runner inserted in the base. Plane base without any obstacle

• Model with shelves and sliding doors




- 1 Top and base, 25 mm thickness
- 2 Inner side panels, MFC 19 mm thickness. Back panel 16 mm thickness
- 3 Shelves are manufactured by mfc 16 mm thickness. Height adjustable every 32 mm
- 4 Ergonomic handles produced with Zamak, aluminium alloy.
- 5 Top security lock. Two positions, open and close. An unique key.
- 6 Levelers supports, inner easy access +20 mm
- 7 Anti skid PVC cap included in the levellers
- 8 2 cable access Ø80 mm, PVC top cover
- 9 Drawers and filing frames with MFC front panel 16 mm thickness
- 10 Drawers and filing frames with telescopic steel runners totally opened
- 11 Anti tilt mechanism (avoiding to open all drawers at the same time)

• Optional steel sides and back cover for desk-support credenza units



- 1 Optional steel side and back cover 2mm thickness. Covered by electrostatic coat, epoxy finish 2° generation polymerized 200°C, grease free and nano-ceramics treatments to get better covering and get so better resistance and long lasting (ant-corrosion coat too). No fingerprints.

• Optional hutches for desk-support credenza units.




- 1 Optional hutch manufactured by MFC 19 mm thickness. Inner space 36,4 x 36,4 mm

■ FINISHES

MFC




White



Maple




Chestnut



Wengue

(see finishes card)



MATERIALS

STORAGE UNITS has been designed to be manufactured with recycled materials 68,44%, danger substances such as chrome, mercury or cadmium are not used in big quantity. Recyclables Aluminium, Steel and Wood 100%. Organic volatile Components. Packages manufactured with recycled carton. Ink thinner free.



PRODUCTION

Energy use is optimized during the production process. Minimum environmental impact. Last generation technological system in coating processes. Painting that have not been used is recovered to use it again. Zero COVs emissions and other contaminant gas. Close water circuit to clean the metals. Heat recovery. Automatic manufacture systems. Cut process is planned.



TRANSPORT

Optimum packaging to reduce space in transport and save energy.



USE

Long lasting use. Spare parts and replacements available. Easy to clean and maintenance.



DISPOSAL

95,54% recyclable. Easy and quick to split **STORAGE UNITS** components. Packages are reuse by our supplier to avoid waste generation. Carton used in packages is recyclable.

CERTIFICATES AND REFERENCES

The different programmes get points in different environmental categories to get the LEED certificate (sustainability, material and resources, water, energy and atmosphere, inner environment quality, innovation and design).



The mark of responsible forestry



PEFC Certificate



EN ISO 14006:2011
ECODESIGN Certificate



UNE-EN ISO 9001:2008
ISO 9001 Certificate



UNE-EN ISO 14001:2004
ISO 14001 Certificate



E1 by EN 13986 Certificate



ACTIU TECHNOLOGICAL PARK
project certified as LEED® GOLD
by U.S. Green Building Council 2011
Leadership in Energy & Environmental Design

■ **ERGONOMICS**

STORAGE UNITS available for all type of users. Perfect for any need and keep user's posture in a natural way without any manual adjustment.

■ **STANDARDS**

STORAGE UNITS has passed tests done in our technical department as well as the tests done in AIDIMA the Technological Institute for furniture. The tests correspond to UNE standards and Filing system cabinets:

- **UNE-CEN/TR 14073-1:2004.** Office Furniture. Filing cabinets. Part 1: Dimensions.
- **UNE-EN 14073-2:2004.** Office Furniture. Filing cabinets. Part 2: security requirements.
- **UNE-EN 14073-3:2004.** Office Furniture. Filing cabinets. Part 3: Tests to determine stability and structure resistance.
- **UNE-EN 14074:2004.** Office Furniture. Desks and filing cabinets. Test to determine resistance and lasting of the mobile components.

■ **ECOLOGY**

ENERGY SAVING

The new technological production system included, reduce the energy resources used to manufacture each component. Materials are very well used to avoid wastes.

RECYCLED AND RECYCABLE MATERIALS

ACTIU environmental policy opts to use recycled materials in those components where functionality and lasting is not a condition. Materials used in Storage units such as aluminium, steel or wood are totally recyclable.

SUSTAINABLE CERTIFICATE

ACTIU has **PEFC and FSC** certificate to proof that the wood used in our products comes from sustainable exploitations and **ECODESIGN ISO 14006 certificate**.

■ REMARKABLE VALUES

1 – Legs covered with epoxy coating, bonding 2nd generation polymerized 200°C. Non-greasy treatments and nano-ceramics application to improve the coating so it becomes more resistance and long-lasting.

2 – Coating 80-90 micron thickness.

This covering guarantees the finish and maintenance of metal structures.

3 – Painting process:

Actiu painting plant has minimum environmental impact against the traditional industry processes.

Treatment is done by polarized coating and compacted with temperature. We get homogeneous and regular application with 98% of painting and the remaining 2% is used to produce other paints. Paints used are COVs free(Volatile Organic Components) which are very dangerous for the environment. All water used in the process is re-used, so we get zero dump. The process is free in heavy metal, phosphate, organic components and DQD(Biochemical demand of Oxygen). The program gives us an exact control of thickness, so it provides us with standard thickness (80-90 micron).

Antibacterial finish

4 – ACTIU has **PEFC and FSC** certificate to proof that the wood used in our products comes from sustainable exploitations and **ECODESIGN ISO 14006** certificate.

5 – Optional accessories fixed to the beams, modesty panels, screens, CPU holders or fixed pedestals.